



### LEDBUBBLE1-C/W

3500K Neutral White 45°

Quicklink: Q17A8

#### General

Colour	White
Construction	Plastic
Dimmable	Yes
IP Rating	IP00

Dimmable Yes

#### Dimensions

Cut Out	25mm (Diameter)
Depth	15mm
Diameter	30mm

#### Electrical

Amperage	350mA
Maximum Wattage	1W

#### Light Characteristics

Beam Angle 45°

The **Bubble LED** is a versatile unit. It can be used separately or together with a light fitting. It has a 25mm cut out and has a high power 1 watt LED. The Warm White Bubbles lumen output is 70lm and the Cool White Lumen output is 100lm.

This LED is available with either a silver or white bezel that has a lens that produces a 45° angle of light. These are ideal for lighting stairs and small areas that require low power usage.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

#### LED Driver Options

- LED Driver (Switching) - Use this driver for on/off control. Cannot be used for dimming.
- LED Driver (Dimming) - For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
- LED Driver (1-10V) - For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- Wise Chameleon (Dimming + Wireless) - This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Chameleon pack.