



## SLL54 COOL 4000K

4000K Cool White 54W  
Quicklink: Q1A58

### General

|              |               |
|--------------|---------------|
| Colour       | White         |
| Construction | Polycarbonate |
| Dimmable     | No            |

Maximum No. Units 7  
Inline

### Dimensions

|             |        |
|-------------|--------|
| Depth       | 45mm   |
| Length      | 1100mm |
| Tube Length | 1180mm |
| Width       | 34mm   |

### Electrical

Maximum Wattage 54W

### Light Characteristics

|                    |                  |
|--------------------|------------------|
| Colour Temperature | 4000K Cool White |
| Halogen Equivalent | 270W             |
| Wattage            |                  |
| Lumens             | 4428 lm          |
| Lumens Per Watt    | 82 lm/W          |

The **Seamless SlimLine - High Output** is the solution for seamless lighting. Featuring a linear lighting fixture casting a clean, continuous light without dark spots, there are currently no other similar products in the market.

Seamless SlimLine consists of a built-in ballast and fluorescent lamp. It is an excellent lighting solution for cove lighting where long seamless lines are required. It is also an excellent choice for display shelves and under bar feature lighting. A diffuser is not available.

If the power cord needs to be extended, then 3-core cable must be used.

### Features

- Dark spot free at the joint with innovative lamp
- Unique design concept to accommodate the newly-developed lamps
- Maximum linkable wattage 400W
- Maximum safety: World class standard, TUV & CE certified and UL listed
- Built in electronic ballast
- Instant on starting, quiet and flicker free
- Allows easy connection, saves installation time
- Protection from lamp end of life (EOL), and cross wiring
- Rigid aluminium extruded body and snap-in mounting brackets

### Specification

- 18,000 hour lamp life
- Frequency range: 50/60Hz
- Power factor: >97%
- Color rendering: Ra>80
- EMI test: EN55015