

# Miniature Round 40 LED

LED 40mm Recessed 12° 350mA  
4000K Cool White 1W

---



## GL019RD SPOT CW

4000K Cool White 1W  
Quicklink: Q1B79

---

### General

Colour	Stainless Steel
Dimmable	Yes
IP Rating	IP68

Dimmable	Yes
LED Type	Luxeon

### Dimensions

Cut Out	31mm (Diameter)
Depth	36mm
Diameter	40mm

### Electrical

Amperage	350mA
----------	-------

### Light Characteristics

Beam Angle	12°
Colour Temperature	4000K Cool White

Discreet yet powerful, this Luxeon LED powered ground light is perfect for dance floors, decking areas, entrance halls and pathways. Indoors or out, the IP68 marine grade stainless steel unit will give a flawless performance for many years of maintenance free operation. Available with a flood or a spot beam angle, means the **GL019** is suitable for any application. With cool glass for added safety.

The fitting comes complete with 1m of 0.35mm red and black teflon cable for wiring.

### Power Supply

A 350mA power supply is required for this fitting. Please use the chart below to determine which is the correct power supply to use:

1 - 6 unit = BULL 350mA 8W
7 - 8 units = DC350mA
9 - 15 units = LED18W 350

For more than 15 fittings, please use more than 1 power supply to cover the load (I.E: 20 units would be 1 x BULL 350MA 8W and 1 x LED18W 350)

This fitting needs to be wired in series.

This fitting outputs **106lx** at 1m.

### LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
  - Dimming - Normal - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
  - Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.
-