



## GL041 FLOOD SSWW

3000K Warm White 50°  
Quicklink: Q1B93

### General

Colour	Stainless Steel
Construction	Stainless Steel
Dimmable	Yes
IP Rating	IP68

Dimmable	Yes
LED Type	Luxeon

### Dimensions

Cable Length	3m
Cut Out	65mm (Diameter)
Depth	43mm
Length	75mm
Width	75mm

### Electrical

Amperage	350mA
Maximum Wattage	3W

### Light Characteristics

Beam Angle	50°
Colour Temperature	3000K Warm White

Three high power LEDs combine to create a strong light output, whilst minimising power consumption. A long maintenance free life is assured, and with its robust stainless steel construction, the **GL041** will remain looking great for many years to come. A low profile design and simple wing springs ensure installation is quick and easy.

### Power Supply

A 350mA power supply is required for this fitting. Please use the chart below to determine which is the correct power supply to use:

1 - 6 unit = BULL 350mA 8W  
7 - 8 units = DC350mA  
9 - 15 units = LED18W 350

For more than 15 fittings, please use more than 1 power supply to cover the load (I.E: 20 units would be 1 x BULL 350MA 8W and 1 x LED18W 350)

### Other things to remember.

This fitting needs to be wired in series.

If using this fitting in an area which is likely to get wet, such as outdoors, bathrooms, saunas and swimming pools, please ensure that the driver is kept in a waterproof enclosure.

Please note the fitting is submersible up to a distance of 2m.

### LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
- Dimming - Normal - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.