

Miniature Guide LED

LED Uplight 36mm Recessed 45° 24V
4000K Cool White 0.5W



GL018 COOL WHITE

4000K Cool White 0.5W
Quicklink: Q1B9C

General

Colour Stainless Steel
Dimmable Yes
IP Rating IP68

Dimmable Yes
LED Type Luxeon

Dimensions

Cut Out 27mm (Diameter)
Depth 37mm
Diameter 36mm

Electrical

Maximum Wattage 0.5W

Light Characteristics

Beam Angle 45°
Colour Temperature 4000K Cool White

This mini (36mm diameter) path marker/ground light is ideal for both domestic and public applications. A modern waterproof design makes this unit a must for decking areas, lobby's and walkways. Combined with exceptionally low power consumption, means this product is cost effective not only to buy, but also to run.

Power Supply

A 24V power supply is required for this fitting. Please use the chart below to roughly determine the correct power supply to use:

1 - 16 unit = DC1024VLS
17 - 36 units = DC21024V
37 - 46 units = RS2524
47 - 90 units = RS5024
91 - 180 units = RS10024

If you require more than the maximum amount of fittings listed above, you will have to use extra power supplies.

Other things to remember.

This fitting needs to be wired in Parallel.

If using this fitting is an area which is likely to get wet, such as outdoors, bathrooms, and saunas. Please ensure that the driver is kept in a waterproof enclosure.

Please note the fitting is submersible up to a distance of 2m.

3m HO5RN-F rubber cable attached

Caution: Voltage drop can occur over long distances. Recommended minimum cable size 0.75mm²
