



TGV103

1 Gang Grey  
Quicklink: Q1CAC

General

Colour	Grey
Construction	Thermoplastic
IP Rating	IP66

Compliance	BS1363 & BS7288
Operating Temperature	0°C ~ 40°C

Dimensions

Depth	75.5mm
Height	142.5mm
Width	117mm

Electrical

Voltage	240V
---------	------

The **Weathersafe Vision Single Gang 13A Fused Spur** is manufactured from tough, durable thermoplastic. It is intended for use in an outdoor environment, or one in which the protection provided by the range is required. Rated at IP66, for protection against water and dust. The product will need to be fitted with waterproof cable or conduit entries to maintain the IP rating once installed. This fused spur unit is ideal for controlling pond pumps, fountains and other permanent outdoor installations. As well as an ON/OFF switch it is fitted with a 13A fuse link and complies to BS 1363.

For more information, please click on the downloads tab.

Features

- Mains isolator switch ensures supply isolation before opening lid
- 13 amp single gang switched socket
- 4 × 20mm cable entries
- Earth terminal and loop terminal in back box
- Impact resistant housing
- Locking boss feature

Specification

- Operating Temperature: -10°C to 45°C
- Type: Fused Spur
- Fully Complies with: BS 1363 (socket outlet conformance) and BS EN 60529 (IP66 rating)