



TGV104

1 Gang Grey
Quicklink: Q1CAD

General

Colour	Grey
Construction	Thermoplastic
IP Rating	IP66

Compliance	BS1363 & BS7288
Operating Temperature	0°C ~ 40°C

Dimensions

Depth	75.5mm
Height	142.5mm
Width	117mm

Electrical

Voltage	240V
---------	------

The **Weathersafe Vision Single Gang 13A RCD Fused Spur** is manufactured from tough, durable thermoplastic. It is intended for use in an outdoor environment, or one in which the protection provided by the range is required. Rated at IP66, for protection against water and dust. The product will need to be fitted with waterproof cable or conduit entries to maintain the IP rating once installed. This RCD fused connection unit gives additional protection against electric shocks and fire risk. The unit will remain latched if the power supply is tripped.

For more information, please click on the downloads tab.

Features

- 4 × 20mm cable entries
- Earth terminal and loop terminal in back box
- Automatically disconnects both Live and Neutral connections leaving Earth connection intact
- Extra fast action - trips out within 40 milliseconds (BS 7288)
- Test button for safety checks
- Contacts remain latched when power supply is temporarily lost
- Impact resistant housing
- Locking boss feature

Specification

- Operating Temperature: -10°C to 45°C
- Type: RCD Fused Spur
- Integral Fuse: BS 1362
- RCD Trip Speed: BS 7288 - 40ms
- Continues to protect with: Lost neutral and pulsating DC earth fault
- IP Rating: IP66
- Fully Complies with: BS 1363 (socket outlet conformance), BS EN 60529 (IP66 rating) and BS 7288 (RCD)