

Extreme Outdoor Sockets

Weathersafe Vision Twin Gang 13A Switched RCD Socket (Passive)

2 Gang Grey



TGV204

2 Gang Grey

Quicklink: Q1CB1

General

Colour	Grey
Construction	Thermoplastic
IP Rating	IP66

Compliance	BS 1363 & BS 7288
Operating Temperature	0°C ~ 40°C

Dimensions

Depth	75.5mm
Height	142.5mm
Width	157mm

Electrical

Voltage	240V
---------	------

The **Weathersafe Vision Twin Gang 13A Switched RCD Socket (Passive)** is manufactured from tough, durable thermoplastic. It is intended for use in an outdoor environment, or one in which the protection provided by the range is required. It is rated IP66, for protection against water and dust. It will need to be fitted with waterproof cable or conduit entries to maintain their IP rating once installed. This unit combines two outdoor switch socket outlets with a non-latching RCD. The contacts break when power supply is temporarily lost, a "safety must" for applications such as power bench tools. The combined unit provides protection against fire hazard and rapid double pole disconnection that can cause electric shock for the appliance(s) and cable(s) connected to it.

For more information, please click on the downloads tab.

Features

- Protects appliances from possible fire hazard
- Extra fast action - trips out within 40 milliseconds (BS7288)
- Test button for safety checks
- Still protects with lost neutral
- Still protects with pulsating DC earth fault currents
- Automatically disconnects both Live and Neutral connections leaving Earth connection intact
- Complies with BS7288 and BS1363
- Earth terminal and loop terminal in back box

Specification

- Operating Temperature: -10°C to 45°C
- Rocker Switch Rating: 240V 13 Amp (3kW)
- Type: Isolated Timer
- IP Rating: IP66
- Fully Complies with: BS 1363 (socket outlet conformance) and BS 7288 (RCD)