

RCD Protection

RCD Single Non-Latching Socket
1 Gang White



MR. RESISTOR[®]
Lighting Specialist Est. 1968



TFA01W

1 Gang White
Quicklink: Q1CC5

The **RCD Single Non-Socket** circuit breaker simply replaces an existing single socket outlet. The contacts break when power supply is temporarily lost.

For more information, please click on the downloads tab.

General

Colour White
Construction Plastic
IP Rating IP00

Compliance BS 1363 & BS 7288
Contact Break Double Pole
Rated Trip Current 30mA
Type Non-Latching

Dimensions

Depth 20mm
Height 85mm
Width 85mm

Electrical

Trip Speed BS 7288 - 40ms
Voltage 240V

Features

- Protects appliances from possible fire hazard
- Manual reset
- Extra fast action - trips out within 40 milliseconds (BS 7288)
- Automatically disconnects both Live and Neutral connections leaving Earth connection intact
- Trips out when the power supply is temporarily lost. A safety must for machine tool applications
- Test button for safety checks
- Still protects with lost neutral
- Still protects with pulsating DC earth fault currents

Specification

- Type: Non-Latching
- Trip Speed: BS 7288 - 40ms
- Contact Break: Double Pole
- Fully Complies with: BS 7288 (RCD performance) and BS 1363 (socket outlet conformance)