

# RCD Protection

RCD Single Non-Latching Socket

1 Gang White



## TFA01W

1 Gang White

Quicklink: Q1CC5

The **RCD Single Non-Socket** circuit breaker simply replaces an existing single socket outlet. The contacts break when power supply is temporarily lost.

For more information, please click on the downloads tab.

### General

Colour	White
Construction	Plastic
IP Rating	IP00

Compliance	BS 1363 & BS 7288
Contact Break	Double Pole
Rated Trip Current	30mA
Type	Non-Latching

### Dimensions

Depth	20mm
Height	85mm
Width	85mm

### Electrical

Trip Speed	BS 7288 - 40ms
Voltage	240V

### Features

- Protects appliances from possible fire hazard
- Manual reset
- Extra fast action - trips out within 40 milliseconds (BS 7288)
- Automatically disconnects both Live and Neutral connections leaving Earth connection intact
- Trips out when the power supply is temporarily lost. A safety must for machine tool applications
- Test button for safety checks
- Still protects with lost neutral
- Still protects with pulsating DC earth fault currents

### Specification

- Type: Non-Latching
- Trip Speed: BS 7288 - 40ms
- Contact Break: Double Pole
- Fully Complies with: BS 7288 (RCD performance) and BS 1363 (socket outlet conformance)