



2426358 NICKEL

4W Nickel
Quicklink: Q1DBD

General

Colour	Nickel
Construction	Steel
Dimmable	No
IP Rating	IP20

Dimmable No

Dimensions

Cut Out	86mm (Diameter)
Diameter	92mm
Minimum Ceiling Depth	150mm
Vertical Rotation	20°

Electrical

Maximum Wattage	4W
Voltage	240V

The **Contract Fire LED Adjustable 240V** downlight does not require a firehood as it is fire rated for up to 90 minutes. These fire rated downlights have many features such as a centralisation ring to ensure a uniform air gap between the body of the fixture and the plasterboard.

Driver Options

Switching Drivers

This fitting comes with a 350mA driver so can be simply wired to a mains supply. The supplied driver is only switchable, on or off. If you need to replace this driver choose a 350mA driver from the Switching range (LED Power Supplies).

Dimming Drivers

If you want this LED to be dimmed you will need to replace the supplied driver with a dimmable driver.

Normal Dimming

To use this fitting with most domestic rotary dimmers simply connect a resistive dimming driver. For lower minimum loads of 20W we recommend a trailing edge dimmer module.

Required parts

- Dimmable LED Driver (LED Power Supplies)
- Resistive Dimmer Module

Wireless Dimming

This unit can switch and dim wirelessly in conjunction with a 24V LED driver.

Required parts

- WISESCENE 350mA (click link on right for associated products)
- 24V DC Transformer
- Wise Switch (any)

1-10V

For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load and the maximum is subject to the drivers load.

Required Parts

- 1-10V 350mA LED Driver
- 1-10V dimmer (click link on right for associated products)