

Globe

Globe 240V
Smoked 300mm



ART1010303 SMOKE

Smoked 300mm
Quicklink: Q2044

General

Cap	ES / E27
Colour	Black
Construction	Thermoplastic
IP Rating	IP44

Dimensions

Diameter	300mm
----------	-------

Electrical

Maximum Wattage	150W
Voltage	240V

The **Globe** fitting is made from moulded and blown PMMA acrylic and comes in four different finishes: clear, smoked (a transparent brown finish), opal (opaque white) and metallic (half clear and half mirrored to reflect light downwards and reduce light pollution). It can be used on its own or combined with a variety of accessories to achieve the following different setups:

Please Note: The Lampholder Base is Included with this Product.

Globe & Base

Any size **Globe** can be combined with a **Globe Post Base** allowing it to be attached to a flat surface, for instance a wall or wall bollard. If this option is chosen a connecting piece of **Globe Post** must be purchased in order to fit the items together. The 200mm and 250mm **Globes** require an 80mm length and the 300mm **Globe** needs a 95mm length.

Globe, Post & Base

There are three different lengths of **Globe Post** that can be combined with the **Globe** and **Globe Post Base** to create a lamp post type fitting.

Globe, Post, Head & Base

The **Globe Post**, **Globe Post Base** and one or more **Globes** can be combined with one of three types of **Globe Post Head** to create a single lamp post with up to three **Globe** light sources. The **Globe Post Heads** are capped so can only fit on to the very top of the **Globe Post**.

Globe, Post, Accessory & Base

The **Globe Post**, **Globe Post Base** and two or more **Globes** can be combined with one of three types of **Globe Post Accessories** to create a single lamp post with up to four **Globe** light sources. The **Globe Post Accessories** are not capped so can be positioned anywhere along the length of the **Globe Post**.

Globe has an opening of 115mm

Globe

Globe 240V
Smoked 300mm

Diameter	d1/d2
∅ 200	92/99
∅ 250	110/118
∅ 300	120/139
∅ 400	165/178
∅ 500	180/189

