

# SlimLine

Seamless SlimLine - Standard Output  
4000K Cool White 35W



## SLL35 COOL 4000K

4000K Cool White 35W

Quicklink: Q21A6

### General

Colour	White
Construction	Polycarbonate
Dimmable	No

Maximum No. Units 17  
Inline

### Dimensions

Depth	44.3mm
Length	1316.5mm
Tube Diameter	34mm
Tube Length	1402mm

### Electrical

Maximum Wattage 35W

### Light Characteristics

Colour Temperature	4000K Cool White
Lumens	3300 lm
Lumens Per Watt	94 lm/W

The **Seamless SlimLine - Standard Output** is the solution for seamless lighting. Featuring a linear lighting fixture casting a clean, continuous light without dark spots, there are currently no other similar products in the market.

Seamless SlimLine consists of a built-in ballast and fluorescent lamp. It is an excellent lighting solution for cove lighting where long seamless lines are required. It is also an excellent choice for display shelves and under bar feature lighting. A diffuser is not available.

If the power cord needs to be extended, then 3-core cable must be used.

### Features

- Dark spot free at the joint with innovative lamp
- Unique design concept to accommodate the newly-developed lamps
- Maximum linkable wattage 400W
- Maximum safety: World class standard, TUV & CE certified and UL listed
- Built in electronic ballast
- Instant on starting, quiet and flicker free
- Allows easy connection, saves installation time
- Protection from lamp end of life (EOL), and cross wiring
- Rigid aluminium extruded body and snap-in mounting brackets

### Specification

- 18,000 hour lamp life
- Frequency range: 50/60Hz
- Power factor: >97%
- Color rendering: Ra>80
- EMI test: EN55015